

SPECIFICATIONS

PR50

PR75

PR95

PULLING UNIT

PULLBACK FORCE

LENGTH

WIDTH

HEIGHT

WEIGHT

ROD DIAMETER

ROD WEIGHT

ROD LENGTH

U.S.	METRIC
99,200 LB	45 T
75 IN	1.91 M
9.8 IN	250 MM
29.5 IN	750 MM
1190 LB	540 KG
1.77 IN	45 MM
26.5 LB	12 KG
39.4 IN	1.0 M

U.S.	METRIC
143,300 LB	65 T
102 IN	2.6 M
15.7 IN	400 MM
31.5 IN	800 MM
3090 LB	1400 KG
1.97 IN	50 MM
33 LB	15 KG
39.4 IN	1 M

U.S.	METRIC
187,400 LB	85 T
71 IN	1.8 M
27.6 IN	700 MM
43.3 IN	1.1 M
7050 LB	3200 KG
1.97 IN	50 MM
33 LB	15 KG
39.4 IN	1 M

ROD MAKE-UP DEVICE

LENGTH

WIDTH

HEIGHT

WEIGHT

23.6 IN	600 MM
15.7 IN	400 MM
19.7 IN	500 MM
408 LB	185 KG

POWER PACK

LENGTH

WIDTH

HEIGHT

WEIGHT

59 IN	1.5 M
38.6 IN	980 MM
37.4 IN	950 MM
1210 LB	550 KG

83 IN	2.1 M
51.2 IN	1.3 M
49.2 IN	1.25 M
3200 LB	1450 KG

POWER

ENGINE

FUEL

COOLING MEDIUM

INJECTION

ASPIRATION

NUMBER OF CYLINDERS

DISPLACEMENT

BORE

STROKE

MANUFACTURER'S GROSS POWER RATING

PER SAE J1995

ESTIMATED NET POWER RATING PER SAEJ1349

RATED SPEED

KUBOTA D1105E	
DIESEL	
LIQUID	
INDIRECT	
NATURAL	
3	
68.6 CU IN	1.1 L
3.07 IN	78 MM
3.09 IN	78.5 MM
26 HP	19.4 KW
25 HP	18.6 KW
3000 RPM	3000 RPM

KUBOTA V3300E	
DIESEL	
LIQUID	
INDIRECT	
NATURAL	
4	
202 CU IN	3.3 L
3.86 IN	98 MM
4.33 IN	110 MM
63 HP	47 KW
59 HP	44 KW
2200 RPM	2200 RPM

HYDRAULIC SYSTEM

MAIN PUMP

MAXIMUM FLOW

MAXIMUM PRESSURE

JAW PUMP

MAXIMUM FLOW

MAXIMUM PRESSURE

22 GPM	83.3 L/MIN
3600 PSI	250 BAR
N/A	N/A
N/A	N/A

32 GPM	121 L/MIN
3600 PSI	250 BAR
22 GPM	83.3 L/MIN
3600 PSI	250 BAR

FLUID CAPACITIES

FUEL TANK

HYDRAULIC RESERVOIR

5.3 GAL	20 L
37 GAL	140 L

10.6 GAL	40 L
53 GAL	200 L

SPECIFICATIONS ARE GENERAL AND SUBJECT TO CHANGE WITHOUT NOTICE. IF EXACT MEASUREMENTS ARE REQUIRED, EQUIPMENT SHOULD BE WEIGHED AND MEASURED. DUE TO SELECTED OPTIONS, DELIVERED EQUIPMENT MAY NOT NECESSARILY MATCH THAT SHOWN. CONTAINS PATENTED FEATURES.